

FTI OPERATIONS, MAINTENANCE, AND REPAIR MANUAL

Super Brute (SB-2A) Cylinder Puller Unit Revision E

FTI Part #2720-107

July 5, 2018



Fatigue Technology (FTI) is the supplier of Split Sleeve Cold Expansion™ (Cx™) systems to the aerospace industry worldwide. These proprietary systems and associated tooling may be covered by patents or agreements owned by, or exclusively licensed to Fatigue Technology. Use of tooling procured from other than a licensed source may constitute patent infringement.

The detailed tooling information in this manual was compiled and written by FTI. The tooling was designed specifically for use with FTI's Cx Systems. FTI cannot be held responsible for damage or injury as a result of operating this equipment if it is used for other than the process intended, with any other tooling not provided by FTI, or not used in accordance with the instructions contained in this manual. To avoid personal injury, please observe all safety precautions and instructions. FTI reserves the right to change specifications or configurations of equipment detailed in this manual as part of our ongoing technical and product improvement programs. If you have any questions about the use or serviceability of this equipment, please contact our Sales Department.

FTI's systems and processes are the subject matter of one or more of the following patents: 4,809,420; 4,885,829; 4,934,170; 5,083,363; 5,096,349; 5,103,548; 5,127,254; 5,218,854; 5,245,743; 5,305,627; 5,341,559; 5,380,136; 5,405,228; 5,433,100; 5,468,104; 6,077,010; 6,183,180; 6,487,767; 6,792,657; 5,129,253; 5,13,898; 6,920,151,24; 5,81,385; 6,931,082,8; 4,68,598; 6,910,539,0; 6,43,231; 6,941,494,6; 6,96,686; 7,85,366; and other patents pending. These systems and processes are tooling critical and must be performed in accordance with FTI's specifications or controlling documents. To ensure proper results from FTI's cold expansion systems and to be licensed to use FTI's patented processes, it is essential that FTI's complete integrated system of tooling be purchased and utilized. The use of tooling purchased from other than a licensed supplier could jeopardize fatigue life enhancement and may constitute patent infringement.

ABOUT FATIGUE TECHNOLOGY

Fatigue Technology (FTI) has provided innovative solutions to fatigue problems in metal structures since 1969. Complete systems of tooling are used worldwide to enhance the fatigue life of holes in airframes, turbine engines, and other critical structures.

The FTI staff of professionals provides a full range of support services including:

- Application engineering
- Detailed project planning, implementation, and management
- On-site assistance, including training and tool room setup
- Complete inventory allowing FTI to respond quickly to customer requirements

A Sales Coordinator is always available to assist with special fatigue enhancement requirements. Please contact FTI with questions at any time.

TABLE OF CONTENTS

SECTION	DESCRIPTION	PAGE
Section 1.0	Introduction.....	1
1.1	About the Super Brute (SB-2A) Cylinder Puller Unit	1
1.2	General Description.....	1
1.3	General Specifications.....	2
Section 2.0	Safety	4
Section 3.0	Puller Unit Operating Instructions.....	6
3.1	Puller Unit Setup Procedure and Operation	6
3.2	Activation of Puller Unit.....	7
3.3	PowerPak Pressure Adjustment.....	7
Section 4.0	Puller Unit Maintenance	8
4.1	General Cleaning.....	8
4.2	Lubrication	8
4.3	Inspection	8
4.4	Disassembly.....	8
Section 5.0	Troubleshooting.....	9
Section 6.0	Illustrated Parts Breakdown.....	13
6.1	SB-2A Puller Unit Diagram	13
6.2	SB-2A Puller Unit Assembly Parts List.....	14
6.3	SB-2A Remote Trigger Assembly and Parts List.....	15

FIGURES

Figure 1.3-1	SB-2A Parts	2
Figure 1.3-2	SB-2A Dimensions	3
Figure 2.0-1	Safety Stickers	4
Figure 2.0-2	PowerPak Air Disconnect.....	4
Figure 3.1-1	Air-Hydraulic Hose Assembly.....	6
Figure 3.1-2	Trigger Assembly with Hoses.....	7
Figure 3.3-1	PowerPak Pressure Adjustment.....	7
Figure 5.0-1	FT-200 PowerPak	9
Figure 5.0-2	Hydraulic Quick Coupler.....	10
Figure 5.0-3	Location of Hydraulic Quick Coupler	10
Figure 5.0-4	Enerpac CT-604 Pressure Relief Tool.....	12
Figure 5.0-5	Trigger Response Valve.....	11
Figure 5.0-6	External Pressure Adjustment Knob.....	12
Figure 6.1-1	SB-2A Diagram.....	13
Figure 6.3.1-1	Diagram of Remote Trigger Assembly.....	15

TABLE OF CONTENTS (Continued)

SECTION	DESCRIPTION	PAGE
TABLES		
Table 1.3-1	SB-2A Specifications.....	3
Table 6.2-1	SB-2A Parts List	15
Table 6.3.1-1	Parts List for Cartridge Trigger Assembly Kit (FTI-CT-RK)	16
APPENDIX		
Appendix	E.C. Declaration of Conformity.....	17

SECTION 1.0: INTRODUCTION

This instruction manual contains information on the operation and maintenance of the Super Brute (SB-2A) Cylinder Puller Unit. To obtain optimum performance and many years of trouble free service, operate the puller unit properly and carefully follow maintenance procedures.

Read this manual before operating the puller unit and retain it for future reference. If requested, FTI will provide this manual in the language of the end-user.

1.1 ABOUT THE SUPER BRUTE (SB-2A) CYLINDER PULLER UNIT

The SB-2A Puller Unit is a powerful, heavy-duty tool specifically designed for use with all Fatigue Technology (FTI) Cold Expansion (CX™) processes. The SB-2A Puller is designed to pull a mandrel through a hole with the pre-lubricated stainless steel split sleeves used in this process, or pre-lubricated bushing used in the ForceMate® (FmCX™) process.

The SB-2A Puller has a maximum pull force of 120,000 pounds (533.79kN) at 10,000 psi (68.95 MPa) pump pressure. The SB-2A is available for cold expanding holes over 3 inches (76mm) in diameter in aluminum, steel, and titanium. Please contact FTI technical support staff for application assistance.

The SB-2A will accommodate tooling for stack-up of approximately 4 inches (102mm).

The SB-2A has a fail-safe air control system that causes the puller retraction cycle to be interrupted whenever the operator releases finger pressure on the trigger or in the event of air or hydraulic hose failure. The puller unit operates in conjunction with FTI's FT-200 PowerPak air-hydraulic power units.

1.2 GENERAL DESCRIPTION


Hydraulic Fluid Requirements	U.S. MIL-H-5606
Operating Hydraulic Pressure	10,000 psi (68.95 MPa)
Pull Force Capacity	120,000 pounds (533.79kN)
PowerPak Air Line Requirements.....	3/8 inch to 1/2 inch (9.5 to 12.7mm) inside diameter
PowerPak Air Flow Requirements.....	90 to 120 psi (0.62 to 0.82 MPa), 50 cfm (1.42m ³ /min)
Actuation.....	Pneumatic
Operation.....	Hydraulic
Compatible PowerPak.....	FT-200
Fail-Safe.....	Air logic safety circuit halts mandrel retraction when trigger is released
Weight.....	113 lbs (51.26 kg.)

*A user-supplied suspension system is required at the end use site. A risk analysis for the suspension is necessary to maintain compliance to end user's standards or directives. All risks involved with the suspension of the Super Brute are the responsibility of the end user. User instructions and training regarding the suspension system are the responsibility of the end user.

1.3 GENERAL SPECIFICATIONS

The SB-2A Puller Unit is designed for applications where the capacity of the Jumbo Brute Puller Unit is exceeded. Actual specifications are shown in Table 1.3-1. Figures 1.3-1 and 1.3-2 also show the SB-2A specifications.

Tooling Selection: The mandrels and nosecaps used with the SB-2A Puller Unit are designed to the specific needs of the customer and the application requirements. Please contact FTI technical support staff for application assistance.




**Figure 1.3-1
SB-2A Parts**

**Table 1.3-1
SB-2A Specifications**

Model Number	Maximum Material Stackup (inch)	Length (inch)	Stroke (inch)	Weight ¹ (lb.)
SB-2A	≈ 4 (102mm)	23.4 (594mm)	6.5 (165mm)	113 (51.26 kg)

Note 1: Puller only, does not include hoses or tooling.



**Figure 1.3-2
SB-2A Dimensions**

SECTION 2.0: SAFETY

When used in accordance with these instructions, the puller unit is safe and easy to use. All general safety precautions associated with hydraulic and pneumatically operated power tools should be observed. Many of these are noted in this section.

The SB-2A Puller Unit is not intended for hand-held operation. The strap handles are provided to carry or to maneuver the puller into position. The sling attachment links are provided for ease of attachment to the operator's hoist apparatus. A sling made from chain, cable, or strap with minimum load capacity certification is highly recommended. DO NOT use rope or other materials not intended for material handling.

Ultimately, operators are responsible for their own safety; however, the following general safety precautions should be observed.

WARNING: HEAVY OBJECT – Mechanical lift only. The suspension system is supplied by the end-user.

1. Operators must read this manual in its entirety before using the Super Brute Puller Unit. Eye and ear protection must be worn while operating the Super Brute. Follow the safety stickers on the Super Brute (see Figure 2.0-1).

Read manual before using



Always wear eye protection




Always wear ear protection



**Figure 2.0-1
Safety Stickers**

2. Remove from mechanical lift when servicing or performing maintenance.
3. Disconnect the air supply when:
 - Maintenance is to be performed.
 - Hydraulic hose is disconnected.
 - PowerPak is not in use.
4. Keep hands away from workpiece/Super Brute Puller interface. Remote Trigger Assembly (2049-007) is provided to allow a safe operating distance.
5. In the event of a ruptured or leaking hydraulic hose, IMMEDIATELY RELEASE THE TRIGGER AND DISCONNECT THE AIR LINE, at the air coupler from the PowerPak (see Figure 2.0-2). Never use your hands to grasp a leaking hose under pressure. The force of escaping hydraulic fluid could cause serious injury.



**Figure 2.0-2
PowerPak Air Disconnect**

6. DO NOT attempt to disconnect the hydraulic hose while it is under pressure.
7. DO NOT expose hoses to potential hazards such as extreme heat or cold, sharp surfaces, or heavy impact.
8. DO NOT allow hoses to kink, twist, curl, or bend so tightly that the oil flow within the hose is blocked or reduced. Periodically inspect the hose for wear or damage that could cause premature failure of the hose and possibly result in injury. Damaged hoses must be replaced immediately.
9. DO NOT use the hose to move attached equipment.
10. Hose material and coupler seals must be compatible with hydraulic fluid that meets the requirements of U.S. MIL-H-5606.
11. Hoses must not come in contact with toxic materials such as creosote-impregnated objects and some paints. Keep couplers and hoses clean and free of paint. Hose deterioration due to chemical degradation may cause the hose to fail under pressure. Damaged hoses must be replaced immediately.
12. Release puller unit trigger when mandrel clears the workpiece or becomes stuck.
13. Before operating pump, make sure all hose connections are tightened securely. DO NOT over tighten.
14. Keep hands away from nosecap assembly while holding nosecap against the workpiece.
15. Hose strain relievers must be placed around hose fittings during use. Damaged strain relievers must be replaced immediately.
16. Before operating the pump, tighten all hose connections using the proper tools. Do not over-tighten the connections. Connections need only be tightened securely and leak-free. Over-tightening may cause premature thread failure or high-pressure fittings to split at pressures lower than their rated capacities.
17. Inspect hydraulic hose for signs of wear (cuts, abrasions or kinks) to the outer shell material. Pump clean oil through the entire length. Pressurize the hose and check for leaks at the crimped connectors, between the hose material and the fitting and between the fitting and the coupler.
18. Do not use in potentially explosive environments.

CAUTION: Operators must read this manual in its entirety before using the SB-2A Puller Unit.
Eye and ear protection must be worn during operation.

SECTION 3.0: PULLER UNIT OPERATING INSTRUCTIONS

Become familiar with these instructions before operating the puller.

Check to assure a sufficient working envelope for unobstructed operation. Note that during puller operation the backside of the puller (hex end) will extend up to the maximum stroke limit.

3.1 PULLER UNIT SETUP PROCEDURE AND OPERATION

Refer to Section 6 (Illustrated Parts Breakdown) for parts identification.

1. Inspect all threads and fittings for signs of wear or damage and replace them if necessary.
2. Remove the protection sleeve on the pull rod and inspect the threads.
3. Test shop air to ensure that air is clean, dry, and between 90 and 120 psi (0.62 and 0.82 MPa) at 50 cfm (1.42m³/min).
4. Uncoil the air-hydraulic extension hose assembly and inspect all threads, couplings, and hoses for damage and degradation. Any damaged component must be replaced immediately.
5. Remove thread protectors from the hydraulic fittings and thread the hydraulic hose fitting from the hose assembly (male) onto the hydraulic fitting of the puller unit. Wipe fittings clean prior to connecting. Make sure to thread couplers completely together. There should be positive contact between the coupler and the hose-fitting flange (you should not be able to insert a piece of paper between the coupler and the hose fitting flange—see Section 5, Problem 2 for more information). Failure to completely tighten the coupler will prevent the puller from returning to the forward (start) position. Strain relievers must be placed on hose fittings during operation. If strain relievers are worn or damaged, they must be replaced immediately.
6. Connect the female air quick disconnect onto the male fitting of the puller unit.
7. Remove thread protectors from the hydraulic fittings and thread the hydraulic hose fitting from the hose assembly (male) onto the hydraulic fitting of the FTI PowerPak (female). Wipe fittings clean prior to connecting. Make sure to thread couplers completely together. Failure to do so will prevent the puller from returning to the forward (start) position. Strain relievers must be placed on hose fittings during operation. If strain relievers are worn or damaged, they must be replaced immediately.
8. Connect the male air quick disconnect attached to the T-fitting into the female coupler of the FTI PowerPak. Figure 3.1-1 shows the hoses and connections.




Figure 3.1-1
Air-Hydraulic Hose Assembly

9. Uncoil the trigger assembly and inspect all threads, couplings and hoses for damage and degradation. Any damaged component must be replaced immediately.
10. Connect the female air quick disconnect of the trigger assembly hose to the male fitting of the FTI PowerPak.
11. Connect the male air quick disconnect into the female coupler at the T-fitting of the air-hydraulic extension hose assembly.
12. Connect the female quick disconnect of a 1/2-inch (12.7mm) ID shop air line onto the male air inlet of the PowerPak. Figure 3.1-2 shows the hoses and trigger assembly.




Figure 3.1-2
Trigger Assembly with Hoses

3.2 *ACTIVATION OF PULLER UNIT*

1. The puller can be activated only when connected to the FTI PowerPak.
2. Activate puller by depressing the trigger on the handle. Hydraulic pressure is transmitted through the hose to the cylinder of the puller, which then retracts the hydraulic piston that performs the cold expansion procedure.
3. Releasing the trigger changes pressure at the pilot valve and stops the pull cycle. Air pressure returns the puller to original position.
4. If the puller fails to operate as detailed above, refer to Section 5 (Troubleshooting).

3.3 *POWERPAK PRESSURE ADJUSTMENT*

1. Activate the puller as described above. Hold the trigger until the PowerPak attains peak pressure and release the trigger two seconds after the peak pressure is reached.
2. If the pressure does not reach 10,000 psi (68.95 MPa), adjust the PowerPak pressure relief valve:
 - a. Squeeze the trigger to activate the puller unit.
 - b. Loosen the locknut and turn the hydraulic pressure valve clockwise until the pressure reaches 10,000 psi (68.95 MPa).
 - c. Tighten the locknut to secure.
 - d. See Figure 3.3-1.




Figure 3.3-1
PowerPak Pressure Adjustment

SECTION 4.0: PULLER UNIT MAINTENANCE

The puller requires routine checking and periodic preventative maintenance to ensure safe, trouble-free operation. No special maintenance is required. The following maintenance actions are suggested.

CAUTION: Before attempting any maintenance operations on the puller, disconnect the PowerPak from the air supply or disconnect the puller from the PowerPak or hand pump.

4.1 GENERAL CLEANING

1. Periodically clean the outer surfaces of the puller unit and PowerPak.
2. When not in use, ensure thread protectors are re-installed on the hydraulic fittings and the pull rod.
3. Keep all hose connections free of dirt and grime. Doing so will dramatically extend the life of pumps and puller seals.

4.2 LUBRICATION

1. There is no internal lubrication requirement for the puller unit.
2. Whenever the puller is to be stored for any length of time, maintain a thin coat of 10-weight oil on the outside of black oxide surfaces.

4.3 INSPECTION

Periodically inspect threaded fittings, hoses, and strain relievers for cracks, leaks or other damage. Repair and replace immediately.

4.4 DISASSEMBLY


The SB-2A Puller Unit is not intended for repair or disassembly in the field. In the event of hydraulic fluid leakage around the seals, the puller should be returned to FTI. Please contact FTI technical support staff for assistance.

SECTION 5.0: TROUBLESHOOTING

This section provides solutions to some basic problems. If you cannot solve your operational problems with the information provided in this section, please contact your nearest FTI representative (see list inside back cover).

NOTE: Should difficulties originate in the PowerPak, consult the specific PowerPak Operations, Maintenance and Repair Manual. Remember, always disconnect the PowerPak main air supply before performing any repair or maintenance.


PROBLEM	CAUSE	SOLUTION
<p>1. PowerPak will not build full hydraulic pressure.</p>	<p>(a) One or more of the key air or hydraulic lines has not been securely connected.</p> <p>(b) Inadequate external pressure.</p> <p>(c) Inadequate air supply.</p>	<p>(a) Check the following hose connections:</p> <ol style="list-style-type: none"> (1) Main air line quick disconnect fitting from shop air system to PowerPak. (2) Hydraulic quick couplings connecting the hoses to the PowerPak manifold and the puller to the hydraulic hoses. (3) Two male/female air line quick disconnect fittings connecting the puller and trigger to the PowerPak manifold. (4) Figure 5.0-1 shows the hose couplers on the FT-200 PowerPak. <p>(b) Adjust external pressure regulator.</p> <p>(c) Check the main air supply has not been interrupted and meets minimum flow requirements (90 psi (0.62 MPa), 50 cfm (1.42m³/min)).</p>




**Figure 5.0-1
FT-200 PowerPak**

CAUTION: Hydraulic oil under extreme pressure may cause serious injuries if not handled carefully. For technical assistance, please contact FTI's technical support staff.

PROBLEM	CAUSE	SOLUTION
<p>2. Puller retracts on first trigger actuation but will not return to start position</p> <p>(b) AND The hydraulic hose is difficult to bend or coil (indicating unrelieved pressure built up in the hose).</p>	<p>(a) The new puller unit requires lubrication through the piston and cylinder.</p> <p>(b) The hydraulic quick coupler line has not been completely tightened at the PowerPak manifold. There should be no space between the PowerPak couple and the hose fitting flange. See Figures 5.0-2 and 5.0-3.</p>	<p>(a) Cycle trigger several times to introduce hydraulic fluid into the cylinder.</p> <p>(b) Once hydraulic pressure has been introduced to the hydraulic hose, the pressure must be relieved before the coupler can be sufficiently tightened.</p>



**Figure 5.0-2
Hydraulic Quick Coupler**



**Figure 5.0-3
Location of Hydraulic Quick Coupler**

- Procedure for relieving hydraulic pressure:
- (1) Disconnect main air supply.
 - (2) Disconnect coupler from PowerPak.
 - (3) Connect Enerpac CT-604 to the coupler and bleed off hydraulic oil to relieve the built-up pressure. Figure 5.0-4 shows the Enerpac CT-604 Pressure Relief Tool.
 - (4) Once pressure is relieved, coupler may be tightened and reinstalled onto PowerPak.
 - (5) Reattach air lines to get puller to return.
 - (6) Check oil level in PowerPak reservoir.



**Figure 5.0-4
Pressure Relief Tool**

PROBLEM**CAUSE****SOLUTION**

3. PowerPak will not generate constant pressure (or hiccups).

(a) Trigger response valve requires adjustment. See Figure 5.0-5.

- (a) Adjustment procedure:
- (1) Loosen locknut on trigger response valve.
 - (2) Using a screwdriver, open screw counterclockwise until PowerPak will not start when puller trigger is depressed.
 - (3) Turn screw clockwise until:
 - PowerPak generates constant pressure when puller trigger is depressed, and
 - PowerPak starts instantly when puller trigger is depressed and stops instantly when released. When the puller trigger is depressed, the PowerPak should be run at the pre-set pressure until the trigger is released.
 - (4) Hold set screw in position and tighten locknut until snug.




Figure 5.0-5
Trigger Response Valve

(b) Inadequate air supply.

(b) Check main air flow for 90 psi (0.62 MPa), 0cfm(1.42m³/min).

PROBLEM**CAUSE****SOLUTION**

4. PowerPak will not operate or maintain sufficient pressure (10,000 psi (68.95 MPa)).

a) Hydraulic pressure requires adjusting. See Figure 5.0-6.

- (a) Adjust PowerPak pressure valve:
- (1) Squeeze trigger on puller unit to activate PowerPak.
 - (2) If pressure does not reach 10,000 psi (68.95 MPa), loosen lock and turn hydraulic pressure control clockwise until pressure reaches 10,000 psi (68.95 MPa).
 - (3) Tighten locknut to secure.

(b) Inadequate air supply.

(b) Increase pressure or flow of available shop air.

- If the PowerPak will not generate or maintain sufficient pressure, the main air line pressure is too low or the PowerPak hydraulic pressure requires adjustment.
- Air pressure requirements: 1/2-inch (12.7mm) ID air line with 90 to 120 psi (0.62 to 0.83 MPa).
- Flow requirements: 40 to 50 cfm (1.13-1.42m³/min).




Figure 5.0-6
External Pressure Regulator Knob

SECTION 6.0: ILLUSTRATED PARTS BREAKDOWN

6.1 SB-2A PULLER UNIT DIAGRAM

A diagram of the SB-2A Puller Unit is shown in Figure 6.1-1, which corresponds to the parts list in Table 6.2-1.




Figure 6.1-1
SB-2A Diagram

6.2 SB-2A PULLER UNIT ASSEMBLY PARTS LIST

The parts list in Table 6.2-1 corresponds to the drawing in Figure 6.1-1 on the previous page.

**Table 6.2-1
SB-2A Parts List**

Reference Number	Description	Part Number	Notes
1	Assembly, SB-2A	2595-002	
2	Cylinder, Hollow Plunger	1045-371	
3	Faceplate, SB-2	2605-001	
4	Screw, Socket Head Cap	1043-005	
5	Tube, Extension SB-2	2606-002	1
6	Piston, SB-2	2604-001	
7	Label, "Caution"	1009-185	
8	Male Quick Disconnect Coupler	1047-036	
9	1/4" Pipe Adapter	1047-029	
10	Cap, Female Dust Cover	1047-009	
11	Attachment, Sling SB-2	2596-001	
12	Nut	1045-172	
13	Screw	1044-048	
14	Washer, Lock	1045-296	
16	Label, "Do Not Strike"	1009-184	
17	Label, "Moving"	1009-258	
18	Adapter, Threaded	5289-004	
19	Assembly, Lifting Handle	1045-469	
---	Assembly, Air-Hydraulic Hose	5628-001	2
---	Assembly, Trigger	2049-007	2
---	Pinwrench, MB	2369-002	2
---	SB-2A Storage Case	1199-086	2
---	Enerpac CT-604 Pressure Relief Tool	1187-770	2,3

Note 1: Some applications remove this piece and install a different Extension Tube.

Note 2: Not shown in assembly illustration.

Note 3: Not included.

6.3 SB-2A REMOTE TRIGGER ASSEMBLY AND PARTS LIST

6.3.1 SB-2A Remote Trigger Assembly

Fatigue Technology. has redesigned the remote trigger assemblies to a cartridge trigger assembly. The new design will reduce the occurrence of trigger air leaks, perform more reliably (better pump actuation), and is easier to maintain. As of June 2005, all remote triggers will have the cartridge trigger assembly.

The previous aluminum trigger can be easily replaced with this improved Brass trigger assembly. The Cartridge Trigger Assembly Kit (FTI-CT-RK)
Puller Trigger Rework Tool Kit (FTI-CT-RKT)

One FTI-CT-RK kit is required for each puller converted. Only one FTI-CT-RKT is required regardless of the number of pullers converted. The FTI-CT-RKT kit includes the tools (punch, tab, etc.) required and detailed instructions on how to perform the modification.

Table 6.3.1-1
Parts List for Cartridge Trigger Assembly Kit (FTI-CT-RK)

Quantity	Item Number	Description	FTI Part Number	Included in Kit #
1	1	Valve, Cartridge Trigger	1187-622	FTI-CT-RK
1	2	Spring, LB Handle	1187-623	FTI-CT-RK
1	3	Retainer, LB Handle	1187-624	FTI-CT-RK
1	4	Sleeve, Puller Handle	3196-001	FTI-CT-RK
1	5	Guard, Remote Trigger Handle	5193-001	None
2	6	Screw, 8-32UNC Modified, 3/16" Long	5195-001	None




Figure 6.3.1-1
Diagram of Remote Trigger Assembly

This page intentionally left blank for two-sided printing.

Appendix
E.C. Declaration of Conformity

This page intentionally left blank for two-sided printing.



FATIGUE TECHNOLOGY
401 Andover Park East
Seattle, Washington 98188-7605
USA

E.C. DECLARATION OF CONFORMITY

Manufacturer: Fatigue Technology
401 Andover Park East
Seattle, WA 98188-7605

Telephone: (206) 246-2010
Fax: (206) 244-9886

Responsible Person in E.C.: Jean-Michel Derisson
4 rue d'Austerlitz
31490 Léguevin
FRANCE

Telephone: 33 5-34-559-916
Fax: 33 5-34-569-047

The undersigned declares that the machinery described:

Type:

Serial Number:

conforms to the following directives:

Council Directive 2006/42/EC (the Machinery Directive)	
ISO 11148-1	Hand-Held Non-Electric Power Tools – Safety Requirements – Part 1
ISO 4413	Hydraulic fluid power – General rules and safety requirements for systems and their components
ISO 4414	Pneumatic fluid power – General rules and safety requirements for systems and their components

and complies with the relevant health and safety requirements.

Jeff Sageman
Logistics Manager

April 30, 2018

Date

This page intentionally left blank for two-sided printing.